

## Cable junction boxes for harsh environment and (or) outdoor installation with box walls without cable entries




- without terminals
- box walls without knockouts
- wall surface can be drilled individually for cable entry max. M 50
- "Outdoor - harsh environment and (or) outdoor"
- colour: black, RAL 9011

wall thickness of the bottom part	3 mm
Degree of protection:	IP 66
Material:	PC-GFS (polycarbonate)
mounting width	230 mm
mounting height	180 mm
max. installation depth	88 mm
width	210 mm
height:	260 mm
depth	117 mm
Weight	1,155 kg
in accordance with	IEC 60 670-22
in accordance with	Det Norske Veritas Certificate No.: E-9149 Germanischer Lloyd Certificate No.: 12 941 - 11 HH Russian Maritime Register of Shipping, technical documentation is approved by the letter No. 250-011-2-39

## Drawings

Dimension drawing



Cable junction boxes for harsh environment and (or) outdoor installation with box walls without cable entries



KF 4350






IP

66

PC




RAL

9011


RAL

9011

Detail mass



box walls



Operating and ambient conditions

Application area	Suitable for outdoor installation (harsh environment and/or outdoor). To reduce the formation and accumulation of condensed water see technical information.
Resistant to occasional cleaning procedures (direct jet)	Resistant to occasional cleaning procedures (direct jet) with high-pressure cleaner without additives, water pressure: max. 100 bar, water temperature: max. 80° C, distance => 0,15 m, in accordance with the requirements IP 69K, enclosure and cable glands at least IP 65
Ambient temperature	Average value over 24 hours + 55 °C Maximum value + 70 °C Minimum value - 25 °C
Fire protection in the event of internal faults	Demands placed on electrical devices from standards and laws Minimum requirements - Glow wire test in accordance with IEC 60 695-2-11: - 650°C for boxes and cable glands - 850°C for parts of insulating material necessary to retain current carrying parts in position

Cable junction boxes for harsh environment and (or) outdoor installation with box walls without cable entries



KF 4350



IP 66

PC

RAL 9011

RAL 9011

Burning behaviour	Glow wire test IEC 60 695-2-11: 960 °C UL Subject 94: V-0 flame resistant self-extinguishing
Degree of protection against mechanical load	IK08 (5 Joule)
Toxic behaviour	halogen-free silicone-free "halogen-free" in accordance with the examination of the cables and insulated wires - corrosiveness of fumes - as per IEC 754-2
Note:	For material properties see technical data.