



JUNCTION BOX

# Abox HA 350



## Abox HA 350

Junction box

**CUSTOMIZABLE**

250 x 250 x 115 mm  
Article number: 48043501

Junction box acc. DIN EN 60670 (VDE 0606), with main cable junction terminal, 35 mm<sup>2</sup>, with IP54 attachment bushes, with blanking plug M40, with twist nipple M50, screw terminal 4-pole 35 mm<sup>2</sup>, input per pole 2 x 35 mm<sup>2</sup>, output per pole 4 x 35 mm<sup>2</sup>, with sealing kit

grey, with 4 pole screw terminal 35 mm<sup>2</sup>



## Technical data

### Measures

Width:	250 mm
Length:	250 mm
Height:	115 mm

### Material

Base:	Polystyrene
Cover:	Polystyrene

### Other attributes

Rated cross section:	35 mm <sup>2</sup>
Tackable:	No
Rated insulation voltage AC:	690 V
Explosion safety:	none
Fire protection:	none
sealable:	No

## Certificates



## Accessory

KVR M50-MGM

KVR M40-MGM

KVR M32-MGM

KVR M25-MGM

DMS M20

AST M40

AST M32

AST M25

AST M20

KVR M50

KVR M40

KVR M32

KVR M25



JUNCTION BOX

# Abox HA 350

Weatherproof:	No
Equipment:	Terminal
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP65 - acc. EN 60529 / DIN VDE 0470-1

KVR M20-GDB

KVR M20

GMU PA M50

GMU PA M40

GMU PA M32

GMU PA M25

GMU PA M20

ADR M50

ADR M40

ADR M32

ADR M25

ADR M20

WST M50

WST M40

WST M32

WST M25

WST M20

## Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%