



JUNCTION BOX

Abox-i 100-L/sw



Abox-i 100-L/sw

Junction box

CUSTOMIZABLE

140 x 140 x 79 mm
Article number: 49191001

Junction box - Industrial Quality - acc. DIN EN 60670 (VDE 0606), Ui=690V, weathering-proof, shock-proof, halogen-free, with IP66 double-membrane seals, M32, seal range 14 - 21 mm

black, without terminal



Technical data

Measures

Width:	140 mm
Length:	140 mm
Height:	79 mm

Material

Base:	polycarbonate, glass fiber-reinforced
Cover:	polycarbonate, glass fiber-reinforced

Other attributes

Entries:	12
Rated cross section:	10 mm ²
Tackable:	No
Rated insulation voltage AC:	690 V

Certificates



Accessory

HandyQuick SQ 31

WST M20/sw

WST M25/sw

WNI M20/sw

WNI M25/sw

DMS M25/sw

DMS M32/sw

KVR M20-MGM/sw

KVR M20-GDB/MGM/sw

KVR M25-MGM/sw

KVR M32-MGM/sw

DMS M32/4

MPS-KRI



JUNCTION BOX

Abox-i 100-L/sw

Explosion safety:	none
Fire protection:	none
sealable:	Yes
Weatherproof:	Yes
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP65 - acc. EN 60529 / DIN VDE 0470-1
Equipment:	None
Color:	black

HandyQuick SQ 52

HandyQuick SQ 32

HandyClip VC 21

HandyClip VC 20

HandyGrip VG 21 w

HandyGrip VG 20 w

HandyGrip VG 21

HandyGrip VG 20

KVR M32-MGM

KVR M25-MGM

KVR M20-GDB/MGM

KVR M20-MGM

VST M32-or

VST M25-or

VST M20-or

AST M32-or

AST M25-or

Environmental attributes

Ambient temperature (24 h):	60 °C
Ambient temperature (max.):	80 °C
Ambient temperature (min.):	-35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%



JUNCTION BOX

Abox-i 100-L/sw

Scale Drawing

